



# OUTDOOR OD-65

65" 3500 nits high brightness double-sided outdoor LCD digital signage



**ALL ALUMINUM**



**SUNLIGHT  
READABLE IMAGE**



**INTELLIGENT THERMAL  
MANAGEMENT**



**WEATHER  
PROOF**



**VANDAL  
RESISTANT**

## FOR MORE INFORMATION

For more information about CNLC, visit our website at [www.cnlcdisplay.com](http://www.cnlcdisplay.com). Copyright © cnlcdisplay. All rights reserved. All specifications and descriptions are subject to change without notice. Reproduction without permission is prohibited.



# SPECIFICATIONS

# DIMENSIONS

Unit:mm[inch]

<b>MODEL</b>		
<b>DISPLAY</b>	LCD Panel Size	65 inches LCD (x2)
	Native Resolution	1920 x 1080
	Brightness (w/o glass)	3500 nits
	Color Depth	10 bits
	Contrast Ratio	4000 : 1
	Response Time (Typ.)	8 ms
	Viewing Angle	178° / 178°
	Light Lifetime (Typ.)	100,000 hrs
<b>TOUCH (Optional)</b>	Detection method	Projected Capacitive Touch Technology
	Input method	Finger and gloved finger
	Noise Shielding	Yes
	Number of simultaneous touches	Max. 40 points
<b>POWER</b>	Power Supply	Internal
	Rated Voltage	100-120V ~ 50/60Hz 200-240V ~ 50/60Hz
	Power Consumption (Typ./ Max)	1400 W / 2200 W [TBD]
<b>MECHANICAL SPECS</b>	Bezel Width (T/B/L/R)	80.0 / 65.3 / 65.3 / 65.3 mm
	Cabinet Color	Black
	Kiosk Dimension (LxHxD)	2175x965x274 mm
	Monitor Weight	150 kg
	Orientation	Portrait
	Glass	Double Laminated Tempered
	Air Vent	Top & Bottom
	Base	539.0 mm H
<b>FEATURE</b>	Language	English
	Image Retention Protection	Yes
	Ambient Light Sensor	Yes
	Power On/Off Scheduling	Yes
<b>INPUT</b>	HDMI 2.1 (HDCP 2.3)	x6 (1080p recommended)
	DisplayPort 1.2	x2
	USB 3.0	x2
	Micro SD Slot	x2
<b>OUTPUT</b>	Audio	x2
<b>EXTERNAL CONTROL</b>	RJ-45	x4 (LAN)
<b>ENVIRONMENT</b>	Operating Temperature	-30° C ~ 50° C
	Storage Temperature	-20° C ~ 60° C
	Humidity	10% ~ 100% RH Non-condensing
	Water and Dust Resistant Design	IP65
<b>INTERNAL PLAYER</b>	Operating System	Android 8.0.0
	Processor	Dual-core A73 and dual-core A53
	Clock Speed	1.5GHz
	Main Memory Interface	DDR4, 2G
	Graphics	Quad-core MaliG51
	Storage	Internal: 16GB eMMC Flash External: Support Micro SD ,Up to 32GB(exFAT) /128GB(FAT32)
Multimedia	4K 10bits VP9/H265/H264 video decoders, up to 60fps 1080P other video decoders (VC-1, MPEG-1/2/4, VP8)	
<b>CERTIFICATION</b>	CE / FCC / RoHS	

